



TECHNICAL DATA SHEET

| ITEM | EN NORMS | RESULT | ASTM NORMS | RESULT | REMARK |
|---------------------------------------|-----------------------|--|--------------|--------------|------------------------|
| Size | EN 427 | 1227*187 mm | ASTM F536 | 1227*187 mm | Pass |
| Dimension Squareness and Straightness | EN 427 | Squareness: 0.18 mm Straightness: 0.07 mm | | | Pass |
| Chemical Resistance | EN 423 | Pass | ASTM F925 | Pass | available upon request |
| Color Fastness to Artificial light | EN 20105:B02 method A | Pass, >=Grade6 | ASTM F1515 | Pass | available upon request |
| Wear Resistance | EN 660-1 | Weargroup: T | | | available upon request |
| Resistant to impact | | | ASTM F1265 | Pass | available upon request |
| Dimensional Stability | E434 | Pass | ASTM F1700 | Pass | |
| Residual Indentation | EN 433 | Pass | ASTM F970 | Pass | |
| Slip Resistance | EN 13893 | Class DS | | | |
| Behaviour to Fire | EN 13501-1 | Bf1-S1 | ASTM E648-06 | Pass/Class 1 | |
| Smoke Density | | | ASTM E662 | Pass, <=450 | |



COMMERCIAL LVT / GLUE DOWN



SPECIFICATIONS

7.37"

48.30"



| | |
|------------------------|-----------------|
| Material | LVT |
| Length x Width (mm) | 1227*187 mm |
| Gloss level | SP 5-7 |
| UV matt coating | Yes, SP coating |
| Pieces / Carton | 16 |
| Cartons / Pallet | 50 |
| Overall thickness (mm) | 2.5 mm |
| Virgin materials | Yes |
| Installation | Glue Down |
| Square Feet / Carton | 39.52 |
| Square Feet / Pallet | 1956 |
| Wear layer | 20 Mil (0.5 mm) |
| Bevel edges on 4 sides | Mirco Bevel |
| Click system | NO |
| Weight Pounds/ Piece | 2.64 |
| Weight Pounds/ Box | 43.47 |

2.5mm



20 Mil wear layer

